

# 1D

## People Counters

### Photoelectric Non-Directional

A cost-effective solution, the SenSource PC-QS06-D is a basic, non-directional wired people counter. Each time its beam is broken, the wall mount LCD will increment by one until reset to zero. The system includes a sensor, one reflector, LCD display and power supply.

To collect and transfer data to a computer using a USB connection, ask about the PC-QS06-R with Count Recorder data logger.



- System includes:
- IR sensor with backplate
  - Reflector
  - LCD Display
  - Power Adapter



NON-DIRECTIONAL  
PEOPLE COUNTER



EASY TO  
INSTALL



COST  
EFFICIENT



## Features

- Miniature sensor with articulating bracket and reflector for easy mounting and alignment
- Modular system installs quickly with very little wiring
- Small modular display mounts almost anywhere
- Magnetic reset to prevent tampering
- 7-year battery backup prevents data loss in case of power failure



LCD Display Side View

## TECHNICAL INFORMATION

PARAMETER	MIN	TYP	MAX
IR Sensor Range	0.1 ft	-	20 ft
IR Sensor Cable Length (6.5 ft supplied)	-	6.5 ft	500 ft
Supply Voltage (12V DC Power Adapter Included)	9 Volts	12 Volts	15 Volts
Supply Current	-	-	50 mA
Enclosure	Sensor: 1.38" x 0.59" x 1.38" / Display: 3.3" L x 3.3" W x 1.2" D		

## ORDERING INFORMATION

ORDERING	
People Counter with LCD Display	PC-QS06-D
People Counter with Count Recorder Data Logger	PC-QS06-R

### SenSource Inc.

3890 Oakwood Ave.

Youngstown, OH 44515

800.239.1226 | info@sensourceinc.com

www.SenSourceInc.com